MSDS

WILD ORCHID BLAST



Product Code K375 Manufacturer: Selden Research Limited

Staden Lane Business Park, Staden Lane,

Buxton, Derbyshire. SK17 9RZ

United Kingdom

Tel: 01298 26226 Fax: 01298 26540 Email: sales@selden.co.uk

2 HAZARDS IDENTIFICATION

Product Name WILD ORCHID BLAST

R12 Extremely flammable.

PRESSURISED CONTAINER - increase in temperature to greater than 50C will cause internal pressure to rise potentially causing

bursting/explosion.

Classification F+;R12.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name EINICS No. CAS No. Content Classification BUTANE 106-97-8 30 - 60% F+·R12 203-448-7 **PROPANE** 200-827-9 74-98-6 30 - 60% F+;R12

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

Move the exposed person to fresh air at once.. Keep the affected person warm and at rest. Get prompt medical attention.. For INHALATION

breathing difficulties oxygen may be necessary.

INGESTION Rinse mouth thoroughly., Drink plenty of water., Get medical attention.

SKIN CONTACT Wash the skin immediately with soap and water., Get medical attention if any discomfort continues.

Promptly wash eyes with plenty of water while lifting the eye lids., Continue to rinse for at least 15 minutes., Get medical EYE CONTACT

attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA Use:, Powder., Dry chemicals, sand, dolomite etc., Water spray, fog or mist.

SPECIAL FIRE FIGHTING Containers close to fire should be removed or cooled with water., Use water to keep fire exposed containers cool and **PROCEDURES**

UNUSUAL FIRE & EXPLOSION

Aerosol cans may explode in a fire. HAZARDS

6 ACCIDENTAL RELEASE MEASURES

Wear necessary protective equipment., Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate., If PERSONAL PRECAUTIONS

leakage cannot be stopped, evacuate area.

ENVIRONMENTAL PRECAUTIONS Any spillage needs to be contained and not allowed to enter water courses

7 HANDLING AND STORAGE

Keep away from heat, sparks and open flame., Avoid spilling, skin and eye contact., Ventilate well, avoid breathing vapours. USAGE PRECAUTIONS

Use approved respirator if air contamination is above accepted level.

USAGE DESCRIPTION Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name Std TWA - 8 hrs STEL - 15 min Notes

BUTANE 1810 mg/m3 WEL 600 ppm 1450 mg/m3 750 ppm **ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Aerosol

ODOUR Characteristic, floral

PHYSICAL DATA COMMENTS Information given relates to total aerosol container contents.

RELATIVE DENSITY 0.55 @ 20C FLASH POINT (°C) - 74 N/A AUTO IGNITION TEMPERATURE (°C) + 405 FLAMMABILITY LIMIT - LOWER(%) 1.8

FLAMMABILITY LIMIT - UPPER(%) 10.0

10 STABILITY AND REACTIVITY STABILITY Stable under normal temperature conditions.



Page 1 of 2



MSDS

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition., Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting/explosion.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates:, Toxic gases/vapours/fumes of:, Carbon monoxide (CO)., Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION SKIN CONTACT EYE CONTACT

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting., Gas or vapour displaces oxygen available for breathing (asphyxiant)., Unconsciousness.

No specific health warnings noted. Irritation of eyes and mucous membranes.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard., Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

UN NO. ROAD UK ROAD CLASS 1950 2

ADR CLASS NO.

2 Class Code:5F Label: 2.1

PROPER SHIPPING NAME

AEROSOLS, FLAMMABLE

UN NO SEA 1950 IMDG CLASS

2.1 N/A 1950

2.1

N/A

IMDG PACK GR. UN NO. AIR AIR CLASS AIR PACK GR.

15 REGULATORY INFORMATION

LABELLING

Extremely Flammable (F+)

RISK PHRASES

R12 Extremely flammable.

SAFETY PHRASES

GUIDANCE NOTES

S16 Keep away from sources of ignition - No smoking., S51 Use only in well-ventilated areas., S2 Keep out of the reach of

STATUTORY INSTRUMENTS

Control of Substances Hazardous to Health., Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Workplace Exposure Limits EH40., Introduction to Local Exhaust Ventilation HS(G)37., CHIP for everyone HSG(108).

16 OTHER INFORMATION GENERAL INFORMATION

The following risk phrases relate to the raw materials in the product and not the product itself:-

REVISION DATE 25/01/2008

REV. NO./REPL. SDS GENERATED RISK PHRASES IN FULL

R12 Extremely flammable.| R12 Extremely flammable.|

